

AIRDUC® PUR 355 SWEEPER REINFORCED

Sweeper hose, heavy duty and reinforced, interior folds


Applications:
municipal vehicle: sweeper, sweeping machine

Properties:
heavy duty and reinforced
highly abrasion resistant
microbe resistant
good resistance to oil, gasoline, and chemicals
very good low temperature flexibility
conforms to RoHS guideline

Temperature range:
-40°F to 195°F

Design, material:
AIRDUC® profile hose
1. spring steel wire firmly embedded in the wall
2. wall: special premium polyurethane (Pre-PUR®)
3. wall thickness 0.06 - 0.07 inch approximate
4. reinforcement of the primary abrasion areas

Delivery variants:
further diameters and lengths available on request
transparent (standard)
special colors: transparent, partially colored, completely colored
customer-specific branding



I.D. in/mm	O.D. in	Pressure psi	Vacuum DIN inHg	Bending Radius in	Weight lbs./ft	Stock length ft	Order No.	Order No.	Article Name
8 / 200-203	8.46	5.30	3.70	7.00	1.780	12	355-0203-5015	35502035015-0000001200	AIRDUC® PUR 355 SWEEPER REINFORCED
8 / 200-203	8.46	5.30	3.70	7.00	1.780	25	355-0203-5015	35502035015-0000002500	AIRDUC® PUR 355 SWEEPER REINFORCED
10 / 254	10.47	4.30	2.20	8.60	2.390	12	355-0254-5016	35502545016-0000001200	AIRDUC® PUR 355 SWEEPER REINFORCED
10 / 254	10.47	4.30	2.20	8.60	2.390	25	355-0254-5016	35502545016-0000002500	AIRDUC® PUR 355 SWEEPER REINFORCED
12 / 305	12.60	3.70	1.75	10.31	3.425	12	355-0305-5015	35503055015-0000001200	AIRDUC® PUR 355 SWEEPER REINFORCED
12 / 305	12.60	3.70	1.75	10.31	3.425	25	355-0305-5015	35503055015-0000002500	AIRDUC® PUR 355 SWEEPER REINFORCED