

CONNECT 240 + 241

Soft sleeve to slide onto connectors or push into pipes

Applications:
industrial vacuum cleaners, vacuum cleaners
municipal vehicle: sweeper, sweeping machine
municipal vehicle: lawn mower, slope mower, leaf blower/ leaf collector
scrubber, floor cleaning machine


Properties:
easily and quickly fitted
re-usable (threaded version)
gas- and liquid-tight as pre-fitted version
highly abrasion resistant
microbe and hydrolysis resistant
good resistance to oil, gasoline, and chemicals
conforms to RoHS guideline

Temperature range:
-40°F to 195°F
short time to 255°F

Design, material:
wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants:
further diameters available on request
black (standard)
special colors: full colored
gas- and liquid-tight as pre-fitted version

Suitable for hose
AIRDUC®: 341 + 345; 350 (AS / AS BLACK / FOOD-AS); 351 + 355 + 356 (FOOD / INOX FOOD-AS / EC); 355 (SWEEPER / SWEEPER REINFORCED / VAC-TRUCK REINFORCED); 355 + 356 AS;
NORPLAST®: 385 AS;
TIMBERDUC®: 533 AS



Recomended adapter-Ø inch	Rec. Adapter length inch	Threading depth of hose inch	Total length (Inch)	Weight lbs/pcs	Suitable for hose I.D. inch	Order No.	suitable for box
pre-fitted							
1.50	1.73	1.57	3.35	0.15	1.50	241-0038-8551	Yes
1.57	1.73	1.57	3.35	0.18	1.57	241-0040-8551	Yes
2.00	1.93	1.61	3.54	0.18	2.00	241-0050-8551	Yes
2.36	1.93	1.61	3.54	0.26	2.36	241-0060-8551	Yes
2.76	2.05	1.73	3.94	0.33	2.76	241-0070-8551	Yes
3.00	2.36	1.85	4.21	0.44	3.00	241-0075-8551	Yes
3.15	2.36	2.05	4.41	0.55	3.15	241-0080-8551	Yes
4.00	2.56	2.24	4.80	0.68	4.00	241-0100-8551	Yes
5.00	2.95	2.44	5.39	1.06	5.00	241-0125-8551	Yes
6.00	3.35	2.76	6.10	1.50	6.00	241-0150-8551	Yes
8.00	3.94	3.15	7.09	2.43	8.00	241-0200-8551	Yes
9.84	4.13	3.54	7.68	3.31	9.84	241-0250-8551	Yes
11.81	4.50	3.94	8.46	4.98	11.81	241-0300-8551	Yes
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345							
1.25	1.73	1.57	3.35	0.15	1.25	241-0032-8500	Yes
1.50	1.73	1.57	3.35	0.19	1.50	240-0038-0000	Yes
1.57	1.73	1.57	3.35	0.19	1.57	240-0040-0000	Yes
2.00	1.93	1.61	3.54	0.20	2.00	240-0050-0000	Yes
2.36	1.93	1.61	3.54	0.26	2.36	240-0060-0000	Yes
2.76	2.05	1.73	3.94	0.32	2.76	240-0070-0000	Yes
3.00	2.36	1.85	4.21	0.44	3.00	241-0075-8500	Yes

3.15	2.36	2.05	4.41	0.55	3.15	241-0080-8500	Yes
4.00	2.56	2.24	4.80	0.68	4.00	241-0100-8500	Yes
5.00	2.95	2.44	5.39	1.06	5.00	241-0125-8500	Yes
6.00	3.35	2.76	6.10	1.50	6.00	241-0150-8500	Yes
8.00	3.94	3.15	7.09	2.43	8.00	241-0200-8500	Yes
9.84	4.13	3.54	7.68	3.31	9.84	241-0250-8500	Yes
11.81	4.50	3.94	8.46	4.98	11.81	241-0300-8500	Yes
Threaded; Suitable for Hose 356							
1.50	1.73	1.57	3.35	0.15	1.50	241-0038-8501	Yes
1.57	1.73	1.57	3.35	0.18	1.57	241-0040-8501	Yes
2.00	1.93	1.61	3.54	0.18	2.00	241-0050-8501	Yes
2.36	1.93	1.61	3.54	0.26	2.36	241-0060-8501	Yes
2.76	2.05	1.73	3.94	0.33	2.76	241-0070-8501	Yes
3.00	2.36	1.85	4.21	0.44	3.00	241-0075-8501	Yes
3.15	2.36	2.05	4.41	0.55	3.15	241-0080-8501	Yes
4.00	2.56	2.24	4.80	0.68	4.00	241-0100-8501	Yes
5.00	2.95	2.44	5.39	1.06	5.00	241-0125-8501	Yes
6.00	3.35	2.76	6.10	1.50	6.00	241-0150-8501	Yes
8.00	3.94	3.15	7.09	2.43	8.00	241-0200-8501	Yes
9.84	4.13	3.54	7.68	3.31	9.84	241-0250-8501	Yes
11.81	4.50	3.94	8.46	4.98	11.81	241-0300-8501	Yes