

CONNECT 270-271

Metal hose connector / reducer


Properties:
easily and quickly fitted
re-usable (threaded version)
conforms to RoHS guideline

Temperature range:
390°F

Design, material:
galvanized sheet metal

Delivery variants:
further diameters available on request
stainless steel (INOX)

Suitable for hose
AIRDUC®: 341 + 345 + 363; 350 (AS / FOOD-AS / AS BLACK); 351 + 355 (FOOD / INOX FOOD-AS / HT / EC); 352 (SE RAILWAY / SE RAILWAY PLUS); 355 (AS / SWEEPER / VAC-TRUCK REINFORCED / VAC-TRUCK ORANGE);
PROTAPE®: 371 HT; 330 (FOOD / AS BLACK / INOX FOOD-AS);
CP: 450 + 455 + 457 + 460 + 461 + 465 + 466 + 467 + 476 + 480 + 481 + 483 + 485 + 486 + 487; 450 + 461 PROTECT; 457 + 459 + 465 EC; 471 + 472 + 475 (INOX / INOX EC);
NORPLAST®: 379 + 383 + 380 + 388 + 389; 384 (AS / FOOD); 384 + 386 + 389 C-AS; 385 (AS / C-AS); 389 PLUS;
TIMBERDUC: 531 - 533 AS;
SuperFlex: 372;
NEO: 390 (ONE / TWO);
SIL: 391 (ONE / TWO)



Suitable for hose I.D. d1 (in) Hose connector	Suitable for hose I.D. d2 (in)	Adapter Length l1 (in)	Adapter Length l2 (in)	Total length l3 (in)	Wall thickness Inch	Weight lbs/pcs	Order No.	suitable for box
2.00	2.00	1.57	1.57	3.50	0.02	0.44	270-0050-0000	Yes
2.36	2.36	1.57	1.57	3.50	0.02	0.44	270-0060-0000	Yes
2.76	2.76	1.57	1.57	3.50	0.02	0.44	270-0070-0000	Yes
3.00	3.00	1.57	1.57	3.50	0.02	0.44	270-0075-0000	Yes
3.15	3.15	1.57	1.57	3.50	0.02	0.44	270-0080-0000	Yes
3.50	3.50	1.57	1.57	3.50	0.02	0.44	270-0090-0000	Yes
4.00	4.00	1.57	1.57	3.50	0.02	0.44	270-0100-0000	Yes
4.33	4.33	1.57	1.57	3.50	0.02	0.66	270-0110-0000	Yes
4.72	4.72	1.57	1.57	3.50	0.02	0.66	270-0120-0000	Yes
5.00	5.00	1.57	1.57	3.50	0.02	0.66	270-0125-0000	Yes
5.12	5.12	1.57	1.57	3.50	0.02	0.66	270-0130-0000	Yes
5.50	5.50	1.57	1.57	3.50	0.02	0.88	270-0140-0000	Yes
6.00	6.00	1.57	1.57	3.50	0.02	1.10	270-0150-0000	Yes
6.30	6.30	1.57	1.57	3.50	0.02	1.10	270-0160-0000	Yes
6.69	6.69	1.57	1.57	3.50	0.02	1.10	270-0170-0000	Yes
6.89	6.89	1.57	1.57	3.50	0.02	1.32	270-0175-0000	Yes
7.00	7.00	1.57	1.57	3.50	0.02	1.32	270-0180-0000	Yes
8.00	8.00	1.57	1.57	3.50	0.02	1.32	270-0200-0000	Yes
8.46	8.46	1.57	1.57	3.50	0.02	1.54	270-0215-0000	Yes
8.86	8.86	1.57	1.57	3.50	0.02	1.54	270-0225-0000	Yes
9.84	9.84	2.36	2.36	5.12	0.02	1.76	270-0250-0000	Yes
10.83	10.83	2.36	2.36	5.12	0.02	1.98	270-0275-0000	Yes
11.81	11.81	2.36	2.36	5.12	0.03	2.20	270-0300-0000	Yes
12.40	12.40	2.36	2.36	5.12	0.03	2.43	270-0315-0000	Yes
12.80	12.80	2.36	2.36	5.12	0.03	2.65	270-0325-0000	Yes
13.78	13.78	2.36	2.36	5.12	0.03	2.87	270-0350-0000	Yes
14.76	14.76	3.15	3.15	6.69	0.03	3.31	270-0375-0000	Yes
15.75	15.75	3.15	3.15	6.69	0.03	3.53	270-0400-0000	Yes
17.72	17.72	3.15	3.15	6.69	0.03	4.63	270-0450-0000	Yes

19.69	19.69	3.15	3.15	6.69	0.03	5.07	270-0500-0000	Yes
Hose reduction								
3.00	2.00	1.57	1.57	5.31	0.02	0.44	271-0075-0000	Yes
3.15	2.76	1.57	1.57	5.00	0.02	0.44	271-0080-0000	Yes
4.00	3.15	1.57	1.57	5.50	0.02	0.44	271-0100-0000	Yes
5.00	4.00	1.57	1.57	5.71	0.02	0.66	271-0125-0000	Yes
6.00	4.00	1.57	1.57	6.89	0.02	0.66	271-0150-0000	Yes
8.00	6.00	1.57	1.57	6.89	0.02	1.10	271-0200-0000	Yes
9.84	8.00	2.36	1.57	8.00	0.02	1.76	271-0250-0000	Yes
11.81	8.00	2.36	1.57	10.43	0.03	2.65	271-0300-0000	Yes
3.15	2.00	1.57	1.57	5.31	0.02	0.44	271-0080-2655	Yes
4.00	2.76	1.57	1.57	6.00	0.02	0.44	271-0100-2660	Yes
5.00	3.15	1.57	1.57	6.89	0.02	0.66	271-0125-2665	Yes
6.00	3.15	1.57	1.57	8.07	0.02	0.88	271-0150-2670	Yes
6.00	5.00	1.57	1.57	5.71	0.02	0.66	271-0150-2671	Yes
8.00	4.00	1.57	1.57	9.64	0.02	1.32	271-0200-2675	Yes
8.00	5.00	1.57	1.57	8.46	0.02	1.32	271-0200-2676	Yes
9.84	5.00	2.36	1.57	11.81	0.02	2.20	271-0250-2680	Yes
9.84	6.00	2.36	1.57	10.63	0.02	1.98	271-0250-2681	Yes
11.81	6.00	2.36	1.57	13.19	0.03	2.87	271-0300-2685	Yes
11.81	9.84	2.36	1.57	7.68	0.03	2.87	271-0300-2687	Yes