

EVA 373 EC

Vacuum cleaner hose, electrically conductive <10⁶ Ohm


Applications:
flexible hose/ ducting for gases and for dust, powder, fibers
industrial vacuum cleaners, vacuum cleaners
explosion hazard area
swimming pool cleaning
scrubber, floor cleaning machine

Properties:
light weight
highly flexible
crush resistant
floatable
good resistance to alkalis and acids
surface resistance <10⁶ Ω
in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: aspiration of combustible dusts (Zone 22 inside), for conveying for non-flammable liquids, for use in zone 1 and 2 (gases), for use in Zone 0 (gases)
conforms to RoHS guideline

Temperature range:
-15°F to 150°F

Design, material:
EVA design
1. self-supporting profile design
2. open profile geometry, wall: EVA

Delivery variants:
further diameters and lengths available on request
black (standard)



I.D. In/mm	O.D. in	Pressure psi	Vacuum DIN inHg	Bending Radius in	Weight lbs./ft	Stock length ft	Order No.	Order No.	Article Name	suitable fo
1 / 25	1.27	14.75	2.11	0.100	-	100	373-0025-1003	37300251003-0000010000	EVA 373 EC	Yes
1.25 / 32	1.59	14.75	2.60	0.160	-	100	373-0032-1003	37300321003-0000010000	EVA 373 EC	Yes
1.5 / 38	1.86	14.75	2.91	0.210	-	100	373-0038-1003	37300381003-0000010000	EVA 373 EC	Yes
- / 40	1.94	14.75	3.15	0.215	-	100	373-0040-1003	37300401003-0000010000	EVA 373 EC	Yes
2 / 50-51	2.38	14.75	3.82	0.295	-	100	373-0050-1003	37300501003-0000010000	EVA 373 EC	No