

CONNECT 240 EC

Soft sleeve to slide onto connectors or push into pipes, electrically conductive

Applications:
industrial vacuum cleaners, vacuum cleaners


Properties:
easily and quickly fitted
re-usable (threaded version)
highly abrasion resistant
microbe and hydrolysis resistant
good resistance to oil, gasoline, and chemicals
electrically conductive wall: electrical and surface resistance <10³ Ω
conforms to RoHS guideline

Temperature range:
-40°F to 195°F
short time to 255°F

Design, material:
Wall of EC version electrically conductive <10³ Ω: electrically conductive premium ester-polyurethane (Pre-PUR®)

Delivery variants:
further diameters available on request
black (standard)
special colors: full colored

Suitable for hose
AIRDUC®: 350 (AS / AS BLACK / FOOD-AS); 351 + 355 (FOOD / INOX FOOD-AS / EC)
TIMBERDUC®: 533 AS



Recomended adapter-Ø inch	Rec. Adapter length inch	Threading depth of hose inch	Total length (Inch)	Weight lbs/pcs	Suitable for hose I.D. inch	Order No.	suitable for box
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345							
1.50	1.73	1.57	3.35	0.21	1.50	2020-02-252020-02-25	Yes
1.57	1.73	1.57	3.35	0.19	1.57	240-0040-1003	Yes
2.00	1.93	1.61	3.54	0.23	2.00	240-0050-1003	Yes
2.36	1.93	1.61	3.54	0.29	2.36	240-0060-1003	Yes
2.76	2.05	1.73	3.78	0.36	2.76	240-0070-1003	Yes